



Hobby Crackle

achieve cracked appearance on various surfaces



Pages: 2

117205.03.2018



Packing
0.5lt



Bases



stir well before
use



Coverage
4 - 8m²/lt.



Drying time
Within 4 - 6
hours.



Application
roller



Application
brush



Description

Acrylic, transparent product, special to achieve cracked appearance on various surfaces. It can be applied on any suitably prepared surface.

Application Instructions

Prepare the surface to be painted and apply Berling's emulsion or acrylic paint to the shade of your choice. This shade will be the substrate of the cracked surface you will create. Then apply a coat of HOBBY Crackle Glaze with a brush to the surface by working the brush in one direction (do not cross the brush and do not pass the Crackle Glaze twice in the same spot) leaving enough of the material on the surface. Let the surface dry thoroughly. Then apply Berling Petite Matt, Eco - Leader professional, Acrylic Professional) emulsion or acrylic paint to the shade of your choice. A few minutes after the application the paint will begin to break by creating the crazing surface.

Surface preparation

The surface to be painted should be dry and clean. Ambient temperature should be at least 5 °C and ambient humidity below 80%. No thinning is required before use.

After use, the remaining paint is removed from paint tools and then cleaned with soap and water. Washings are handled in accordance with applicable legislation and local regulations.

Technical characteristics

- **Binder:** Copolymer dispersion of acrylic esters.
- **VOC:** 15g/lit (Maximum Volatile Organic Compounds content ready for use).
- **Specific gravity:** $1,00 \pm 0,02$ grams /cm³ (ISO 2811).
- **Coverage:** 4 - 8m² /lt.
- **Thinning:** The product is ready for use and does not require thinning.
- **Application:** The product is applied with a brush.
- **Drying time:** Within 4 - 6 hours. (These times may be extended depending on the temperature)
- **Recoat:** Recoat only with emulsion or acrylic paint after 4 to 6 hours on one coat. (These times may be prolonged depending on temperature and humidity).

Storage

Keep containers air- tight closed and protected from frost. For long-term storage, it is best to keep the product indoors in order to avoid exposure to very low or high temperatures and high humidity.

Transport

The product is not classified as hazardous during road transport in accordance with ADR.

ACCORDING TO 2004/42 /EC

PHASE II, Subcategory I, Decorative finishing Effects,
VOC Limit Value = 200gr/lit,
Maximum VOC Value= 15gr/lit (ready to use product).

Packing
0.5lt



Bases
—



stir well before
use



Coverage
4 - 8m² /lt.



Drying time
Within 4 - 6
hours.



Application
roller



Application
brush



All the above information is based on laboratory tests and long-term experience of the company's scientific personnel. Product quality is guaranteed by our operational system, which is based on the requirements of ISO 9001, ISO 14001 and OHSAS 18001 Standards and EMAS Regulation. As producers we don't take any responsibility for any damage that may caused in cases that the product hasn't been used for the appropriate application and according to the application instructions.

Page 2 to 2

BERLING SA
Paint Industry

Inofita Viotias, P.C. 32011
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr / info@berling.gr


BERLING
Color has a Name!