



STONE VARNISH

Stone Varnish



Color has a Name!



05.2019 v02

Packaging: 0.75lt | 4lt

Description

Special acrylic impregnating varnish which penetrates even the smallest pore of stone, offering a uniform surface. Suitable for indoor and outdoor use for Karistos, Pilion states, etc.

Purpose of use

Painting stone surfaces.

Product characteristics

- High penetrability.
- High resistance to weather condition changes
- Easy application.

Shades

It is available in colorless.

Performance.

5-9m²/L, depending on the absorptivity of the stone surface.

Recommended application systems

Pilion and Karistos slates etc.

New surfaces

Stage	Description	Coatings
Preparation	At new surfaces clean well removing dust	
Primer	Not required	
Final coating	Stone Varnish	2-3 coats

Old, already painted surfaces

Stage	Description	Coatings
Preparation	In case of already painted with stone varnish surfaces, rub first with sandpaper and then clean thoroughly	
Primer	Not required	
Final coating	Stone Varnish	2-3 coats

Application Conditions

The application is carried out at an ambient temperature of at least 10 °C and a maximum relative humidity of 80%. In the case of exterior surfaces, do not apply if there is a chance of rain in the next 48 hours.

Technical specifications

V.O.C	Up to 720gr/lit (Maximum Volatile Organic Compounds content ready for use).
Specific gravity	0,86 ± 0,03gr/cm ³ (ISO 2811).
Viscosity	15-30 sec, 25°C (Flow cup, 4 DIN 53211).
Performance	5-9m ² /lit, depending on absorbency and surface type.
Thinning	The product is ready for use and does not require thinning.
Application	The product is applied by brush or roller.
Drying time	Touch dry after 1 to 2 hours. (These times can be prolonged depending on temperature and humidity).
Recoat	After 16 hours. (These times may be prolonged depending on temperature and humidity).
Tool cleaning	Clean tools with White Spirit.

ACCORDING TO 2004/42/EC

PHASE II, Subcategory h, Binding Primers, Max VOC content limit value =750gr/lit, max VOC content value= 720gr/lit (ready to use product).

Storage

Store indoors to avoid exposure to high or low temperature and high humidity conditions. Avoid heat and radiation sources, static electricity and storage near food. Keep cans tightly closed. After opening the can use the product in a short period of time. Close well again.

Safety Instructions- Prevention of environmental harming

Wear protective gloves, goggles and face/eye protection equipment. Do not eat, drink when handling the product. Avoid unnecessary exposure. Wash hands with suitable cleaning products.

Clean tools with White Spirit. Do not put residual paint down the kitchen sink or toilet or into a waste bin. Empty cans with paint residues should be handled the same way and disposed according to local Regulations. You should ask for advice for the local government section responsible for the collection and disposal of waste.

Keep out of reach of children. Always read the can label before use.

For further information ask for the Safety Data Sheet of the product.

All the above information is based on laboratory tests and long-term experience of the company's scientific personnel. Product quality is guaranteed by our operational system, which is based on the requirements of ISO 9001, ISO 14001 and OHSAS 18001 Standards and EMAS Regulation. As producers we don't take any responsibility for any damage that may be caused in cases that the product hasn't been used for the appropriate application and according to the application instructions.

BERLING SA

Paint Industry

Inofita Viotias, P.C. 32011

tel.: +30 22620 31663, fax.: +30 22620 31293

www.berling.gr / info@berling.gr

