



## Shades

Available in white and can be tinted in many shades using Berling's tinting system.  
(After tinted the product should be stirred for 5 - 10 minutes).

## Labeling - Environmental Effect Prevention

The product is classified as Corrosive. Causes burns. Avoid contact with skin and eyes.  
In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin, wash with plenty of water. Wear suitable protective clothing, gloves and eye / face protection. In case of accident or if you feel unwell, seek medical advice immediately.



C: Corrosive

## Recommended personal protective equipment

Wear protective clothing, gloves and glasses. Make sure there is sufficient ventilation.

## Storage

Keep cans air - tight sealed and protect from frost. For long - term storage keep the product indoors in order to avoid its exposure to very low or very high temperatures as well as high humidity conditions.

## Transportation

Not dangerous while transportation according to the ADR regulation.

## ACCORDING TO 2004/42/EK

PHASE II, Subcategory I, Decorative effect coating, Max VOC content limit value = 200gr/lit,  
Max VOC content = 5gr/lit (ready to use product).

All the above information is based on laboratory tests and long-term experience of the company's scientific personnel. Product quality is guaranteed by our operational system, which is based on the requirements of ISO 9001 and ISO 14001 Standards and EMAS Regulation.

As producers we don't take any responsibility for any damage that may be caused in cases that the product hasn't been used for the appropriate application and according to the application instructions.

## BERLING SA Paint Industry

Inofita Viotias, P.C. 32011,  
tel.: +30 22620 31663, fax.: +30 22620 31293  
[www.berling.gr](http://www.berling.gr) / [info@berling.gr](mailto:info@berling.gr)

